



» In mechanically swaged fittings, high pressure presses and precision dies cause the metal of the socket to flow around the wires and strands to result in optimum compactness and strength with minimum weight

Open Swaged Sockets (Metric)

Part #	Strand Diameter (mm)	Weight Each (kg)	Dimensions (mm)					After Swage (mm)
			C	D	H	M	N	
MOS - 13	13	0,94	51,0	25,4	25,4	14,2	51,0	23,1
MOS - 14	14	2,12	60,5	30,2	31,8	17,3	57,0	29,5
MOS - 16	16	2,05	60,5	30,2	31,8	17,3	57,0	29,5
MOS - 19	19	3,62	70,0	35,1	38,1	20,3	70,0	36,1
MOS - 22	22	5,23	79,5	41,1	44,5	23,9	82,5	39,4
MOS - 25	25	8,07	93,5	51,0	51,0	26,9	95,5	45,7
MOS - 28	28	11,8	105	57,0	57,0	30,2	108	52,0
MOS - 32	32	16,1	117	63,5	63,5	31,0	119	58,5
MOS - 35	35	19,8	127	63,5	63,5	35,1	133	65,0

Open Swaged Sockets (Imperial)

Part #	Diameter (in)	Weight Each (lb)	Dimensions (in)					After Swage (in)
			C	D	H	M	N	
MOS - 300	1/2	2.08	2.00	1.00	1.00	0.56	1.96	0.91
MOS - 302	9/16	4.67	2.38	1.19	1.25	0.68	2.21	1.16
MOS - 303	5/8	4.51	2.38	1.19	1.25	0.68	2.21	1.16
MOS - 304	3/4	7.97	2.75	1.38	1.50	0.80	2.69	1.42
MOS - 306	7/8	11.52	3.13	1.62	1.75	0.94	3.20	1.55
MOS - 308	1	17.35	3.69	2.00	2.00	1.06	3.68	1.80
MOS - 310	1 1/8	25.25	4.12	2.25	2.25	1.19	4.18	2.05
MOS - 312	1 1/4	35.56	4.59	2.50	2.50	1.27	4.68	2.30
MOS - 314	1 3/8	43.75	5.25	2.50	2.50	1.46	5.25	2.56